

Model: R5200



- Model: R5200
- Category: Roll to Roll UV Printer
- Printing size: 5.2m
- Media thickness: 1-2mm
- Print technology: Drop-on-demand Piezo Electric Inkjet
- Print head type: Kyocera kj4a
- Print head controls: Print head temperature and voltage are software adjustable
- Ink characteristics: UV curing ink
- Ink reservoir: Refillable on the fly while printing/2000 ml
- Drying system: LED lamp
- Rip software: Onyx
- Color management: lcc based color, Curves adjustment, Density adjustment
- File format: Tiff, Jpeg, Postscript 3, Eps and Pdf
- Power supply: 50/60hz 220v (10%) >30A Single phase
- Operation Environment: Temperature 20°C to 28°C
- Humidity: 40% to 60%
- Interface: Fast Standard USB port
- Print model: Single Direction & Bi-direction
- Printing speed (2 row head):
 - In production mode up to 70 - 74 sq.m/h (color printing)
 - In quality mode up to 46 - 50 sq.m/h (color printing)
 - In ultra quality mode up to 35 - 39 sq.m/h (color printing)
- Colors: 4 colors (CMYK) or 6 color (CMYK Lc Lm) white can be optional
- Outdoor life: 3 years (use docan ink)
- Dimension: 8.5*2.0*2.16m
- Weight: 7780kg
- Warranty: 1 year limited warranty
- Medias: Wall paper, flex banner, PET, Black film, Vinyl etc.

Model: R3200



- Model: R3200
- Category: Roll to Roll UV Printer
- Printing size: 3.2m
- Media thickness: 1-2mm
- Print technology: Drop-on-demand Piezo Electric Inkjet
- Print head type: Kyocera kj4a
- Print head controls: Print head temperature and voltage are software adjustable
- Ink characteristics: UV curing ink
- Ink reservoir: Refillable on the fly while printing/2000 ml
- Drying system: UV/LED lamp (UV lamp with 3 power levels)
- Rip software: Onyx
- Color management: lcc based color, Curves adjustment, Density adjustment
- File format: Tiff, Jpeg, Postscript 3, Eps and Pdf
- Power supply: 50/60hz 220v (10%) >30A Single phase
- Operation Environment: Temperature 20°C to 28°C
- Humidity: 40% to 60%
- Interface: Fast Standard USB port
- Print model: Single Direction & Bi-direction
- Printing speed (2 row head):
 - In production mode up to 66 - 70 sq.m/h (color printing)
 - In quality mode up to 42 - 46 sq.m/h (color printing)
 - In ultra quality mode up to 30 - 34 sq.m/h (color printing)
- Colors: 4 colors (CMYK) or 6 color (CMYK Lc Lm) white can be optional
- Outdoor life: 3 years (use docan ink)
- Dimension: 5.8*1.8*1.6m
- Weight: 3895kg
- Warranty: 1 year limited warranty
- Medias: Wall paper, flex banner, PET, Black film, Vinyl etc.